

GSM Fixed Wireless Phone, GSM desktop phone with SIM card, GSM telephone

for Use in: Remote and mountainous areas

Homes and workplaces

For public use in shops and bars

Call-Centers,

Offices,

Ships, trains and long distance buses

Comes with external antenna to improve signal in poor reception areas

Use indoor or out: powered by either battery or AC adapter

Backlit LCD display shows caller ID and time

Features

- 1. Support GSM900/1800Mhz; GSM850/900/1800/1900Mhz optional**
- 2. Caller ID**
- 3. Dot-matrixed display with Spanish,English, Chinese, optional**
- 4. SMS function**
- 5. IP No. Setting**
- 6. Software upgrade jack**
- 7. Data service, Support CSD and GPRS class 10/8. Connect PC by USB port**
- 8. Call in / Call out /Call divert/ Call waiting limitation function**
- 9. Lock up function: SIM card, network, cell and operated company**
- 10. Local No. / direct No. / limited No. Setting**
- 11. Speed dial function**
- 12. Redial function**
- 13. Support three-way conference call**
- 14. Save more than 100 SMS on the phone**
- 15. 7-level headphone volume and silence adjustable**

- 16. Speaker Phone**
- 17. Low-power indicator**
- 18. Storage 20 missed call or received calls and the last ten dialed number**
- 19. Voice mail function**
- 20. Packing Size (mm): 220*160*53**
- 21. Support STK1114**
- 22. Emergency call: At off-hook or hand-free state, can calling emergency number without**

Operating Requirements

- 1. Operating Freq.: GSM900-1800Mhz/850-1900Mhz automatically switch**
- 2. Normal operation temperature: -30 ---70**
Restricted operation temperature: -30 ---80
Storage temperature: -40 ---85
- 3. Environment noise: Below 60dB(A)**
- 4. Support SIMCard 1.8V/ 3V**
- 5. Channel interval: 200KHz**
- 6. Receive sensitivity: <-100dBm**
- 7. Relative humidity: 45%~95%**
- 8. Atmosphere pressure: 86~106Kpa**
- 9. Support for software upgrade on line**
- 10. AC power voltage: 220V?à22V, Freq.: 50Hz**
- 11. GPRS multi-slot class 10/8**
GPRS mobile station class B
- 12. Compliant to GSM phase 2/2+**
-Class 4(2W@850/900MHz)
-Class 1(1W@1800/1900MHz)
- 13. Control via AT commands (GSM 07.07, 07.05 and SIMCOM enhanced AT Commands)**
- 14. Phone: DC 9V 1000mA**
- 15. Battery: 3, 6V 1300mAH Ni-MH rechargeable battery (accessory)**
 - 1. With batteries, standby time is more than 72h**
 - 2. With battery, Call time is more than 4h**

Applications

- 1) For public use as payphones**
- 2) For office and home use**
- 3) For rural and mountainous areas**
- 4) For mobile carriages, like ships, automobiles and trains**
- 5) For those places where hardwire-line telephone service is unavailable**

Content:

Item Qty : GSM FWP
User's Manual
UK,USA ,europe, australia

G.W./unit: 1kg
Dimension: 25*18*7cm